

# Levaslip 411

## Leveling Agent

### DESCRIPTION

Levaslip 411 is a modified polysiloxane which improves good slip and leveling properties.

### TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: modified polysiloxane
Appearance	: colorless to slight yellow clear liquid
Non-volatile content	: 6.7 - 7.7%
Solvent	: toluene
Specific gravity	: 0.86 - 0.89
Refractive index	: 1.485 - 1.495 (25°C)

### FEATURES

- To enhances paint flow and leveling, imparts smooth surface.
- It can be reduces crater, fish eyes, pinholes
- Good compatibility.
- If need to re-coat, please test recoatability.

### APPLICATIONS

solvent-based coatings

### DOSAGE & USE

- 0.05 - 0.5% based on total formulation.
- It is recommended to carry out serial test of Levaslip 411 at various level to obtain optimum dosage.

### PACKAGE

Net Weight: 25 kg

### STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C and 40°C.

### SAFETY

- As it contains a solvent, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.