

## Levaslip 433

### Leveling Agent

#### DESCRIPTION

Levaslip 433 is a slip and leveling agent for solvent-based coatings. It assists substrate wetting and improves levelling and mar resistance.

#### TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: modified polysiloxane
Appearance	: slight yellow clear liquid
Non-volatile content	: 49 - 51%
Solvent	: xylene / isobutanol
Specific gravity	: ca. 0.93
Refractive index	: 1.454 - 1.464 (25°C)

#### FEATURES

- It's lower surface tension, it can improve substrate wetting, flowing and smooth surface and eliminate orange peel, crater.
- To reduce friction coefficient, improve scratch resistance, mar resistance and anti-blocking.
- Good compatibility.
- To prevent floating in tinted base.
- If need to re-coat, please test recoatability.

#### APPLICATIONS

solvent-based coatings

#### DOSAGE & USE

0.2 - 0.5% based on total formulation. It is recommended to carry out serial test of Levaslip 433 at various level to obtain optimum dosage.

#### PACKAGE

Net Weight: 180 kg / 25 kg

#### STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C and 40°C.

#### SAFETY

- As it contains solvents, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.