

Levaslip 435

Leveling Agent

DESCRIPTION

Levaslip 435 is a silicone leveling agent, suitable for solvent-base coatings.

TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: modified polysiloxane
Appearance	: clear to slight hazy liquid
Non-volatile content	: > 98%
Specific gravity	: 0.950 - 0.978

FEATURES

- Effectively reduces coating troubles such as poor adhesion, pinhole and crater when substrates are contaminated by oil, grease or silicone releasing agent, so-called anti-silicone effect.
- Excellent leveling, slip and releasing effect combined with reactive hydroxyl group, can be utilized in heat resistant non-stick cooking wares.
- Enhances softness, water repellence, slip and wash durability of fabrics.
- Recoatability is not good.

APPLICATIONS

- solvent-based coatings
- solvent-based ink

DOSAGE & USE

- 0.05% - 0.30% based on total formulation.
- Please check the optimum dosage in each individual application.

PACKAGE

Net Weight: 25 kg

STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C and 40°C.

SAFETY

- The product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.