

# Levaslip 466

## Leveling Agent

### DESCRIPTION

Levaslip 466 is a silicone leveling agent, suitable for solvent-based coatings.

### TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: modified polysiloxane
Appearance	: slight yellow liquid
Non-volatile content	: 23.5 - 25.5%
Solvent	: xylene / ethyleneglycol monobutylether
Specific gravity	: ca. 0.9
Refractive index	: 1.458 - 1.468 (25°C)

### FEATURES

- Good substrate wetting, improved leveling and flowing, prevent surface defects.
- Good slip performance.
- Good compatibility with mostly resins.
- If need to re-coat, please test recoatability.

### APPLICATIONS

solvent-based coatings

### DOSAGE & USE

- 0.1 - 0.5% based on total formulation with sufficient mixing.
- Please check the optimum dosage in each individual application.

### PACKAGE

Net Weight: 180 kg / 25 kg

### STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C and 40°C.

### SAFETY

- As it contains a solvent, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.