

Levelol 491

Leveling Agent

DESCRIPTION

Levelol 491 is a silicone-free leveling agent, to provide good flowing, leveling and dearator performance.

TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: acrylic copolymer
Appearance	: colorless clear liquid
Non-volatile content	: 98.5 - 100%
Specific gravity	: ca. 1.04
Dynamic viscosity	: 15000 - 40000 cP(25°C)

FEATURES

- It is a polymeric leveling agent can be eliminate surface defect.
- It does not influence the intercoat adhesion.
- It is light stable, hydrolysis resistant, it's used for plasticizing coatings.
- The composition of Levelol 491 conforms to the recommendation **of Germany's Bgw** on surface coatings for food containers and packaging.

APPLICATIONS

- powder coatings
- alkyd / melamine
- acrylic / melamine
- polyester / melamine
- can & coil coatings

DOSAGE & USE

- 0.4 - 2.0% based on total formulation. Mix well before use.
- Please check the optimum dosage before use.

PACKAGE

Net Weight: 25 kg

STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C and 40°C.

SAFETY

- The product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.