

Levelol 495

Leveling Agent

DESCRIPTION

Levelol 495 is a silicone-free flow and leveling agent used in solvent based coatings.

TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition : acrylic copolymer
Appearance : colorless to slight yellow
clear liquid

None-volatile content: 48 - 52%

Solvent : xylene

Specific gravity : ca. 0.95

Refractive index : 1.478 - 1.488 (25°C)

FEATURES

- To improve leveling flowing and foam-releasing.
- No side-effect the intercoat.
- It is light stable, hydrolysis resistant and does not migrate from paint film.
- Due to its nonvolatility, it can plasticize the paint films of N/C and A/C lacquer.

APPLICATIONS

solvent-based coatings

DOSAGE & USE

- 0.2 - 1.0% based on total formulation.
- Please test compatibility and optimum dosage before practical use.

PACKAGE

Net Weight: 25 kg

STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C and 40°C.

SAFETY

- As it contains a solvent, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.