

Defom 5600

Defoamer

DESCRIPTION

Defom 5600 is an excellent compatibility polysiloxane defoamer.

TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: modified polysiloxane
Appearance	: colorless clear liquid
Solvent	: aromatic hydrocarbon sobutanol
Specific gravity	: 0.83 - 0.87

FEATURES

- Good bubble releasing in high build two-component polyurethane.
- To preventing foaming of solvent based systems caused by mechanical forces such as mixing, production and application.
- It can be reducing fish-eye, pinhole and crater defects.
- Good compatibility with major solvent-based coatings.

APPLICATIONS

solvent-based coatings

DOSAGE & USE

- 0.1 - 0.7% based on total formulation.
- Please check the optimum dosage in each individual and test compatibility prior to use.
- Where post-addition is necessary, it is recommended to incorporate Defom 5600 with sufficient mixing.

PACKAGE

Net Weight: 180 kg / 25 kg

STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed a dry and well-ventilated place.
- Stored between 0°C and 40°C.

SAFETY

- As it contains a solvent, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.