

# Defom 5700

## Defoamer

### DESCRIPTION

Defom 5700 is a modified silicone defoamer, exhibit excellent anti-foaming and defoaming property.

### TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: modified polysiloxane
Appearance	: clear liquid
Non-volatile content	: 4.5 - 5.5%
Solvent	: diisobutylketone
Specific gravity	: ca. 0.81
Refractive Index	: 1.409-1.412(25°C)

### FEATURES

- To prevent foaming caused by mechanical force such as mixing, production and application.
- It's good compatibility, no surface defect, like fish eye, pinhole, crater etc.
- Good defoaming and leveling in UV system
- To exhibit excellent anti-foaming in dip coatings.

### APPLICATIONS

- UV curable coatings
- epoxy coatings

### DOSAGE & USE

- 0.01 - 0.2% based on total formulation.
- Please check the optimum dosage in each individual and test compatibility prior to use.
- Where post-addition is necessary, it is recommended to incorporate Defom 5700 with sufficient mixing.

### PACKAGE

Net Weight: 165 kg / 25 kg

### STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C and 40°C.

### SAFETY

- As it contains a solvent, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check to MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.