

Defom 6500

Defoamer

DESCRIPTION

Defom 6500 is a bubble releasing, anti-foaming agent for solvent based coatings.

TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: modified polysiloxane
Appearance	: colorless to slight yellow clear liquid
Non-volatile content	: 0.85 - 1.05%
Solvent	: cyclohexanone
Specific gravity	: 0.92 - 0.96
Refractive index	: 1.443 - 1.453 (25°C)

FEATURES

- To prevents foaming of solvent based coatings caused by mechanical force such as mixing, production and application.
- To exhibits excellent anti-foaming function in dipping coatings.

APPLICATIONS

- solvent-based coatings
- solvent-free epoxy coatings

DOSAGE & USE

- 0.1 - 1.0% based on total formulation
- Incorporated before grinding or processing to achieve optimum effect.
- Where post-addition is necessary, it is recommended to incorporate Defom 6500 with sufficient mixing.

PACKAGE

Net Weight: 180 kg / 25 kg

STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed a dry and well-ventilated place.
- Stored between 0°C and 40°C.

SAFETY

- As it contains a solvent, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.