

Defom 6700

Defoamer

DESCRIPTION

Defom 6700 is an anti-foaming agent, it can also reduce surface tension to provide good film surface.

TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: polysiloxane
Appearance	: clear liquid
Non-volatile content	: > 99.5%
Specific gravity	: 0.94 - 0.97
Surface tension	: ca. 21.1 dynes/cm (25°C)
Refractive index	: 1.4025 - 1.4045 (25°C)

FEATURES

It's lowest surface tension, preventing foaming caused by mechanical forces such as mixing, production and application.

APPLICATIONS

solvent-based coatings and ink

DOSAGE & USE

- For air releasing : 0.1 - 0.2% based on total formulation.
- For leveling : 0.02 - 0.10% based on total formulation.
- Extremely low dosage, suggest to pre-dilute before use.
- Please check the optimum dosage, recoability and compatibility prior to use.

PACKAGE

Net Weight: 200 kg / 25 kg

STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed a dry and well-ventilated place.
- Stored between 0°C and 40°C.

SAFETY

- As it contains a solvent, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.