

Levelol 835

Leveling Agent

DESCRIPTION

Levelol 835 is a silicone-free flow and leveling agent.

TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: acrylic copolymer
Appearance	: colourless to yellow clear liquid
Non-volatile content	: 49.5 - 51.5%
Solvent	: aromatic hydrocarbon solvent
Specific gravity	: ca. 0.94
Refractive index	: 1.481 - 1.491 (25°C)

FEATURES

- Excellent flow and leveling properties.
- Good compatibility and recoatability.
- It is light stable, hydrolysis resistant and does not migrate from paint film.
- Can be improve impact and flexibility.

APPLICATIONS

solvent-based coatings

DOSAGE & USE

- 0.1 - 1.0% based on total formulation. Please test compatibility before use.
- Is advisable to be combined with resin prior to pigmentation to ensure uniform distribution.

PACKAGE

Net Weight: 200 kg / 25 kg

STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C and 40°C.

SAFETY

- As it contains a solvent, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.