

Levaslip 836

Leveling Agent

DESCRIPTION

Levaslip 836 is a slip and leveling agent for solvent based coatings. Good slip performance.

TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: modified polysiloxane
Appearance	: colourless to slight yellow, clear liquid
Non-volatile content	: 23 - 25%
Solvent	: xylene / isobutanol
Specific gravity	: 0.86 - 0.90
Refractive index	: 1.450 - 1.460 (25°C)

FEATURES

- To reduce coefficient of friction, improve scratch resistance, mar resistance and blocking resistance.
- To improve orientation of matting agents in flat coatings.
- To enhance aluminium flake orientation in metallic coatings.
- Good compatibility.
- Good finger mark resistance.
- If need to re-coat, please test recoatability.

APPLICATIONS

solvent-based coatings

DOSAGE & USE

- 0.1 - 0.5% based on total formulation with sufficient mixing.
- Please check the optimum dosage in each individual application.

PACKAGE

Net Weight: 25 kg

STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C and 40°C.

SAFETY

- As it contains a solvent, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.