

Defom 8700

Defoamer

DESCRIPTION

Defom 8700 is a silicone-free type defoamer and leveling agent used in solvent-based paints.

TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: foam destroying polymer, silicone-free
Appearance	: colorless to slight yellow clear liquid
Non-volatile content	: 48 - 52%
Solvent	: ethyl acetate
Specific gravity	: 0.92 - 0.98

FEATURES

- In manufacturing sanding sealer containing zinc stearate by high speed dispersion, entrapped air and foam are stabilized by zinc stearate due to its surface active property.
- Defom 8700 helps de-aeration of thick film and coatings on porous substrate.
- It can be also exhibits leveling function and prevents the formation of crater or pinhole.

APPLICATIONS

- N/C Lacquer
- sanding sealer
- acid-cure amino
- unsaturated polyester coatings
- UV-curable coatings

DOSAGE & USE

- 0.2 - 1.0% based on total formulation.
- In sanding sealer, add before dispersion to achieve best antifoaming and defoaming performance.
- Please check compatibility of Defom 8700 in each system.

PACKAGE

Net Weight: 180 kg / 25 kg

STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed a dry and well-ventilated place.
- Stored between 0°C and 40°C.

SAFETY

- As it contains a solvent, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.