

Levaslip 876

Leveling Agent

DESCRIPTION

Levaslip 876 is a good compatibility polysiloxane surface additive to provide good substrate wetting, anti-cratering performance, slip and excellent leveling for wood coatings, and general industrial coatings.

TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: modified polysiloxane
Appearance	: colorless to slight yellow clear liquid
Non-volatile content	: 12.0 - 14.0%
Solvent	: xylene / ethylene glycol phenyl ether
Specific gravity	: ca. 0.93
Refractive index	: 1.49 - 1.50 (25°C)

FEATURES

- To provide good substrate wetting and good anti-crater.
- To reduce coefficient of friction, improves scratch resistance, mar resistance and anti-blocking properties.
- If need to re-coat, please test recoatability.

APPLICATIONS

solvent-based coatings

DOSAGE & USE

0.2 - 0.5% based on total formulation. It is recommended to carry out serial test of Levaslip 876 at various level to obtain optimum dosage.

PACKAGE

Net Weight: 180 kg / 25 kg

STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C and 35°C, above 35°C may due to slightly haze, but not affect performance.

SAFETY

- As it contains a solvent, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.