

Levaslip 879

Leveling Agent

DESCRIPTION

Levaslip 879 is a slip and leveling agent. It provides excellent slip performance.

TYPICAL PROPERTIES

These values are used as reference. For detail product specifications, please contact our distributor or sales department.

Composition	: modified polysiloxane
Appearance	: colorless to slight yellow clear viscous liquid
Non-volatile content	: >95 %
Specific gravity	: 1.02 - 1.03
Reflective index	: 1.445 - 1.449 (25°C)

FEATURES

- Excellent slip performance.
- Lower surface tension, improves substrate wetting.
- It can be reduce coefficient of friction and improve scratch resistance.
- Good compatibility in various non-aqueous coatings.
- If need to re-coat, please test recoatability.

APPLICATIONS

- non-queueous
 - ◆ N/C lacquer
 - ◆ 2K PU
 - ◆ A/C lacquer
- aqueous coatings

DOSAGE & USE

- 0.1 - 0.5% based on total formulation. It is recommended to carry out serial test of **Levaslip 879** at various levels to obtain optimum dosage.
- For easy to use, please predilute **Levaslip 879** before use.

PACKAGE

Net Weight: 25 kg

STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C and 40°C, below 5°C the product would become solid.
- Warm to room temperature and mix well before use. The efficiency is not influenced.

SAFETY

- The product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.